

# Kitemark™ Certificate

This is to certify that:

Dempsey Dyer Limited  
Unit 11-13  
Langthwaite Business Park  
South Kirkby  
Pontefract  
WF9 3AP  
United Kingdom

Holds Certificate Number:


KM 60733

In respect of:

**BS 7412 / PAS 24**  
**Enhanced Security PVCU Windows Fabricator**

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.



For and on behalf of BSI:

Gary Fenton, Global Product Certification Director

First Issued: 09/11/2001

Latest Issue: 11/01/2016



# Kitemark™ Certificate

No. KM 60733

## **BS 7412:2007 / PAS 24:2012 - Enhanced security performance requirements for window assemblies.**

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Deceuninck Limited under Certificate Number KM 33904.

<b>System(s):</b>	<b>Contemporary 3000 PVC-U Window System</b>	
<b>Fabrication and Installation:</b>	Fabricated and installed in accordance with the latest issue(s) of the following controlled manual(s):  Contemporary3000 Technical File Deceuninck Limited Contemporary 3000 Casement Windows Security Manual	
<b>Fabrication Options</b>	Welded transoms/mullions, tee and/or cruciform joints only	
<b>Glazing Options:</b>	Double Glazed only Internally Glazed only	
<b>Ventilation:</b>	None	
<b>Window Type and approved hardware:</b>	Casement windows	Locking: Yale shootbolt espag, Yale Encloser twin cam espag, Maco M-SPAG or Maco R A I L  Hinges: Yale F2, Securistyle Defender, Securistyle Defender plus, Cotswold HS Sinindex,  Handles: Greenteq Alpha, Fab & Fix Connoisseur Off-Set  Other: Greenteq hinge protector; GT Stay Guard; GT Securi-Clip; Fab & Fix Q318 Restrictor
	Tilt/Turns	Locking: Maco face fit, Maco concealed gearing, Siegenia face fit, Siegenia concealed gearing.  Handles: Greenteq Alpha, Sensei T/T Handle  Other: GT Securi-Clip
	Fixed windows	
	Multilight windows consisting of opening light(s) and/or fixed light(s)	

First Issued: 09/11/2001

Latest Issue: 11/01/2016

Page: 2 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.

# Kitemark™ Certificate

No. KM 60733

## Size Limitations and Performance Characteristics

### Contemporary 3000 PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m <sup>2</sup> ) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for windows with approved sash profiles:									
Projecting top hung Reinforced*	1200	1200	-	24"	-	3	E1050	A5	2000
Projecting side hung Reinforced*	700	1400	-	16"	-	4	7A	A5	2000
Projecting side hung Defender Plus hinge, reinforced*	900	1400	-	16"	-	4	7A	A5	2000
Tilt/Turns Steel reinforced sash	1500	1500	-	-	-	4	8A	A5	2000
Overall dimensions for windows with approved outer frame profiles:									
Fixed Reinforced*	2000	2000	4.00	-	-	3	9A	A5	2000
Overall dimensions for approved outer frames & transom/mullion profiles:									
Multilights steel T/M Reinforcement	2400	2400	3.36	-	1400	4	9A	A5	2000

\* unless otherwise stated reinforcement can be either TCI, aluminium or steel.

First Issued: 09/11/2001

Latest Issue: 11/01/2016

Page: 3 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.

# Kitemark™ Certificate

No. KM 60733

## **BS 7412:2007 / PAS 24:2012 - Enhanced security performance requirements for window assemblies.**

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Deceuninck Limited under Certificate Number KM 33904.

<b>System(s):</b>	<b>Heritage 2800 PVC-U Window System</b>	
<b>Fabrication and Installation:</b>	Fabricated and installed in accordance with the latest issue/s of the following controlled manual(s):  Heritage 2800 Technical File Deceuninck Limited Heritage 2800 Casement Windows Security Manual	
<b>Fabrication Options:</b>	Welded and/or mechanically fixed transoms/mullions, tee and/or cruciform joints	
<b>Glazing Options:</b>	Double Glazed only Internally Glazed only	
<b>Ventilation:</b>	None	
<b>Window Types:</b>	Casement windows	Locking: Yale shootbolt espag, Yale Encloser twin cam espag, Maco M-SPAG or Maco R A I L  Hinges: Yale F2, Securistyle Defender, Securistyle Defender plus, Cotswold HS Sinidex,  Handles: Greenteq Alpha, Fab & Fix Connoisseur Off-Set  Other: Greenteq hinge protector; GT Stay Guard; GT Securi-Clip; Fab & Fix Q318 Restrictor
	Tilt/Turns	Locking: Maco face fit, Maco concealed gearing, Siegenia face fit, Siegenia concealed gearing.  Handles: Greenteq Alpha, Sensei T/T Handle  Other: GT Securi-Clip
	Fixed windows	
	Multilight windows consisting of opening light(s) and/or fixed light(s)	

First Issued: 09/11/2001

Latest Issue: 11/01/2016

Page: 4 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.

# Kitemark™ Certificate

No. KM 60733

## Size Limitations and Performance Characteristics

### Heritage 2800 PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m <sup>2</sup> ) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for windows with approved sash profiles:									
Projecting top hung Reinforced*	1200	1200	-	24"	-	3	E1050	A5	2000
Projecting side hung Reinforced*	700	1400	-	16"	-	4	7A	A5	2000
Projecting side hung Defender Plus hinge, reinforced*	900	1400	-	16"	-	4	7A	A5	2000
Tilt/Turns Steel reinforced sash	1500	1500	-	-	-	4	8A	A5	2000
Overall dimensions for windows with approved outer frame profiles:									
Fixed Reinforced*	2000	2000	4.00	-	-	3	9A	A5	2000
Overall dimensions for approved outer frames & transom/mullion profiles:									
Multilights steel T/M Reinforcement	2400	2400	3.36	-	1400	4	9A	A5	2000

\* unless otherwise stated reinforcement can be either TCI, aluminium or steel.

First Issued: 09/11/2001

Latest Issue: 11/01/2016

Page: 5 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.

# Kitemark™ Certificate

No. KM 60733

## **BS 7412:2007 / PAS 24:2012 - Enhanced security performance requirements for window assemblies.**

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Deceuninck Limited under Certificate Number KM 33904.

<b>System(s):</b>	<b>Traditional 2500 PVC-U Window System</b>	
<b>Fabrication and Installation:</b>	Fabricated and installed in accordance with the latest issue of the following controlled Technical manual:  Traditional 2500 Technical File Deceuninck Limited Traditional 2500 Casement Windows Security Manual	
<b>Fabrication Options:</b>	Welded transom/mullion tee joints only	
<b>Glazing Options:</b>	Double glazed only Internally glazed only	
<b>Ventilation:</b>	None	
<b>Window Types:</b>	Casement windows	Locking: Yale shootbolt espag, Yale Encloser twin cam espag, Maco M-SPAG or Maco R A I L  Hinges: Yale F2, Securistyle Defender, Securistyle Defender plus, Cotswold HS Sinidex,  Handles: Greenteq Alpha, Fab & Fix Connoisseur Off-Set  Other: Greenteq hinge protector; GT Stay Guard; GT Securi-Clip; Fab & Fix Q318 Restrictor
	Tilt/turn Windows	Locking: Maco face fit, Maco concealed gearing, Siegenia face fit, Siegenia concealed gearing.  Handles: Greenteq Alpha, Sensei T/T Handle  Other: GT Securi-Clip
	Fixed windows	
	Multilight windows consisting of opening light(s) and/or fixed light(s)	

First Issued: 09/11/2001

Latest Issue: 11/01/2016

Page: 6 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.

# Kitemark™ Certificate

No. KM 60733

## Size Limitations and Performance Characteristics

### Traditional 2500 Series PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m <sup>2</sup> ) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Sash dimensions for windows with approved sash profiles:									
Projecting top hungs Reinforced*	1200	1200	-	24"	-	3	E1050	A5	2000
Projecting side hungs Reinforced*	700	1400	-	16"	-	4	7A	A5	2000
Projecting side hung Defender Plus hinge, reinforced*	900	1400	-	16"	-	4	7A	A5	2000
Tilt/Turns Steel reinforced sash	1500	1500	-	-	-	4	8A	A5	2000
Overall dimensions for windows with approved outer frame profiles:									
Fixed Reinforced*	2000	2000	4.00	-	-	3	9A	A5	2000
Overall dimensions for approved outer frames & transom/mullion profiles:									
Multilights steel T/M Reinforcement	2400	2400	3.36	-	1400	4	9A	A5	2000

\* unless otherwise stated reinforcement can be either TCI, aluminium or steel.

First Issued: 09/11/2001

Latest Issue: 11/01/2016

Page: 7 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.  
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.  
A member of BSI Group of Companies.