

Kitemark™ Certificate

This is to certify that:

Deceuninck Limited
Porte Marsh Industrial Estate
Stanier Road
Calne
SN11 9PX
United Kingdom

Holds Certificate Number:

KM 633952


In respect of:

BS 8529 / PAS24
Enhanced Security Composite Door System Supplier

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:



Gary Fenton, Global Product Certification Director

First Issued: 08/12/2015

Latest Issue: 08/12/2015



Kitemark™ Certificate

No. KM 633952

BS 8529:2010 / PAS 24:2012 - General and enhanced security performance requirements for Composite door assemblies.

This Certificate covers the following residential door system design specification. Only those components that have been approved in accordance with the Kitemark scheme requirements can be incorporated within the system(s) detailed.

Deceuninck Composite Residential Door System

Fabricated and installed in accordance with the latest issue of the following Deceuninck Limited manual(s):
Composite Door Technical File

System description

The door assemblies are open in, hinged on outer frame or mullion, Doorco Slab, cassette glazed with BS EN 1279-2 compliant IGU(s), laminated on the outer pane, with either standard or mechanically fixed low threshold. Doors are classified as either D K or D KT.

Hardware	Locking:	Auto slam Winkhaus AV2, Winkhaus AV2F, Yale Mantis 3, Winkhaus Cobra F, Paddock Lockmaster, Mila Master. Maco C-TS
	Hinges:	SFS D2 Dynamic Hinge, Mila Evolution, Greenteq Sigma composite door hinges
	Handle:	Greenteq Stainless Steel pull handle
	Other:	Fab n Fix Nu-mail, Mila Prostyle or Omega letterboxes, Stormguard AM3 threshold, Stormguard ICD/Deceuninck 3306 drip bar

Size Limitations and Performance Characteristics

Door Type	Length (mm) Maximum	Height (mm) - Maximum (including sill)	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009 (except *)
Overall dimensions for doors with approved outer frame and sash profiles:						
Single leaf doors	1025	2080	4	4A	A3	1200

First Issued: 08/12/2015

Latest Issue: 08/12/2015

Page: 2 of 2

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 845 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.