

Kitemark™ Certificate

This is to certify that:

Dempsey Dyer Limited
Unit 11-13
Langthwaite Business Park
South Kirkby
Pontefract
WF9 3AP
United Kingdom

Holds Certificate Number:

KM 60733

In respect of:

BS 7412 / PAS 24
Enhanced Security PVCU Windows Fabricator

This issues the right and licence to use the Kitemark in accordance with the Kitemark Terms and Conditions governing the use of the Kitemark, as may be updated from time to time by BSI Assurance UK Ltd (the "Conditions"). All defined terms in this Certificate shall have the same meaning as in the Conditions.

The use of the Kitemark is authorized in respect of the Product(s) detailed on this Certificate provided at or from the above address.

For and on behalf of BSI:



Chris Lewis - Certification Director, Product Certification

First Issued: 2001-11-09
Latest Issue: 2019-08-01

Effective Date: 2019-08-01
Expiry Date: 2022-07-31



Kitemark™ Certificate

No. KM 60733

BS 7412:2007 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Deceuninck Limited under Certificate Number KM 33904.

System(s):	Contemporary 3000/5000 PVC-U Window System	
Fabrication and Installation:	Fabricated and installed in accordance with the latest issue(s) of the following controlled manual(s): Contemporary 3000/5000 Technical File	
Fabrication Options	Welded transoms/mullions, tee and/or cruciform joints only	
System Description:	The windows are double or triple glazed, internally beaded, multipoint locking with welded transoms/mullions and/or tee joints.	
Ventilation:	None	
Window Type and approved hardware:	Casement windows	Locking: Yale shootbolt espag, Yale Encloser twin cam espag, Maco M-SPAG Maco R A I L, Kenrick Easyfit, Kenrick Excalibur or Roto TSL espag Hinges: Yale F2, Securistyle Defender, Securistyle Defender plus, Cotswold HS Sinidex, Nico Handles: Greenteq Alpha, Fab & Fix Connoisseur Off-Set Other: Greenteq Delta hinge protector & Nico Xtrabolt; GT Stay Guard; GT Securi-Clip or Snap-Lok (optional*); Fab & Fix Q318 Restrictor, Sash Seal, GT Bow Constrictor.
	Tilt/Turns	Locking: Maco face fit, Maco concealed gearing, Siegenia face fit, Siegenia concealed gearing, Roto Designo II concealed gearing Handles: Greenteq Alpha, Sensei T/T Handle Other: GT Securi-Clip or Snap-Lok (optional*) *Only where IGU size is increased by ≥ 4 mm
	Fixed windows	
	Multilight windows consisting of opening light(s) and/or fixed light(s)	

First Issued: 2001-11-09

Latest Issue: 2019-08-01

Effective Date: 2019-08-01

Expiry Date: 2022-07-31

Page: 2 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Kitemark™ Certificate

No. KM 60733

Size Limitations and Performance Characteristics Contemporary 3000/5000 PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m ²) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Overall dimensions for windows with approved sash profiles:									
Projecting top hungs Reinforced*	1200	1200	-	24"	-	3	E1050	A5	2000
Projecting top hungs Reinforced*	1200	1500	-	24"	-	4	E1050	A5	2000
Projecting side hungs Reinforced*	700	1400	-	16"	-	4	7A	A5	2000
Projecting side hung Defender Plus hinge, reinforced*	900	1400	-	16"	-	4	7A	A5	2000
Tilt/Turns Steel reinforced sash	1500	1500	-	-	-	4	8A	A5	2000
Tilt/Turns Slim Sash	1200	1500	-	-	-	4	A9	A5	2000
Overall dimensions for windows with approved outer frame profiles:									
Fixed Reinforced*	2000	2000	4.00	-	-	3	9A	A5	2000
Overall dimensions for approved outer frames & transom/mullion profiles:									
Multilight – steel transom/mullion reinforcement 3238	2400	2400	3.36	-	1400	4	9A	A5	2000
Multilight – steel transom/mullion reinforcement 3242	2400	1500	3.5	-	1500	4	A9	A5	2000

* unless otherwise stated reinforcement can be either TCI, aluminium or steel.

First Issued: 2001-11-09

Latest Issue: 2019-08-01

Effective Date: 2019-08-01

Expiry Date: 2022-07-31

Page: 3 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 60733

BS 7412:2007 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Deceuninck Limited under Certificate Number KM 33904.

System(s):	Heritage 2800 PVC-U Window System	
Fabrication and Installation:	Fabricated and installed in accordance with the latest issue(s) of the following controlled manual(s): Heritage 2800 Technical File	
Fabrication Options:	Welded or mechanically jointed, frames/sashes/transoms/mullions, tee and/or cruciform joints only	
System Description:	The windows are double or triple glazed, internally beaded, multipoint locking only.	
Ventilation:	None	
Window Types:	Casement windows Including flush Sash	Locking: Yale shootbolt espag, Yale Encloser twin cam espag, Maco M-SPAG Maco R A I L Maco MKII, Kenrick Easyfit, Kenrick Excalibur or Roto TSL espag Hinges: Yale F2, Securistyle Defender, Securistyle Defender plus, Cotswold HS Sinidex, Nico Handles: Greenteq Alpha, Fab & Fix Connoisseur Off-Set Other: Greenteq Delta hinge protector and Nico Xtrabolt.; GT Stay Guard; GT Securi-Clip or Snap-Lok (optional*); Fab & Fix Q318 Restrictor, Sash Seal, GT Bow Constrictor.
	Tilt/Turns	Locking: Maco face fit, Maco concealed gearing, Siegenia face fit, Siegenia concealed gearing, Roto Designo II concealed gearing Handles: Greenteq Alpha, Sensei T/T Handle Other: GT Securi-Clip or Snap-Lok (optional*) *Only where IGU size is increased by $\geq 4\text{mm}$
	Fixed windows Multilight windows consisting of opening light(s) and/or fixed light(s)	

First Issued: 2001-11-09

Latest Issue: 2019-08-01

Effective Date: 2019-08-01

Expiry Date: 2022-07-31

Page: 4 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 60733

Size Limitations and Performance Characteristics

Heritage 2800 PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m ²) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Overall dimensions for windows with approved sash profiles:									
Projecting top hungs reinforced*	1200	1200	-	24"	-	3	E1050	A5	2000
Projecting top hungs reinforced*	1200	1500	-	24"	-	4	E1050	A5	2000
Flush Sash top hung TCI reinforced	1200	1200	-	24"	-	4	E900	A4	1600
Flush Sash top hung Steel reinforced	1200	1200	-	24"	-	4	E900	AE	2400
Projecting side hungs reinforced*	700	1400	-	16"	-	4	7A	A5	2000
Projecting side hung Defender Plus hinge, reinforced*	900	1400	-	16"	-	4	7A	A5	2000
Flush Sash side hung TCI reinforced	700	1310	-	16"	-	4	E900	A4	1600
Flush Sash side hung Steel reinforced	700	1310	-	16"	-	4	E900	AE	2400
Flush Sash French Casement TCI reinforced	1400	1310	-	16"	-	3	6A	B5	2000
Tilt/Turns Steel reinforced sash	1500	1500	-	-	-	4	8A	A5	2000
Overall dimensions for windows with approved outer frame profiles:									
Fixed Reinforced*	2000	2000	4.00	-	-	3	9A	A5	2000
Overall dimensions for approved outer frames & transom/mullion profiles:									
Multilights steel T/M Reinforcement	2400	2400	3.36	-	1400	4	9A	A5	2000

* unless otherwise stated reinforcement can be either TCI, aluminium or steel.

First Issued: 2001-11-09

Effective Date: 2019-08-01

Latest Issue: 2019-08-01

Expiry Date: 2022-07-31

Page: 5 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

Kitemark™ Certificate

No. KM 60733

BS 7412:2007 / PAS 24:2016 - Enhanced security performance requirements for window assemblies.

This Certificate covers the fabrication of windows from the range of profiles and components supplied by Deceuninck Limited under Certificate Number KM 33904.

System(s):	Traditional 2500 PVC-U Window System	
Fabrication and Installation:	Fabricated and installed in accordance with the latest issue of the following controlled Technical manual: Traditional 2500 Technical File	
System Description:	The windows are double or triple glazed, internally beaded, multipoint locking with either welded or mechanically jointed transoms/mullions and/or tee joints.	
Ventilation:	None	
Window Types:	Casement windows	Locking: Yale shootbolt espag, Yale Encloser twin cam espag, Maco M-SPAG Maco R A I L, Kenrick Easyfit, Kenrick Excalibur or Roto TSL espag Hinges: Yale F2, Securistyle Defender, Securistyle Defender plus, Cotswold HS Sinidex, Nico Handles: Greenteq Alpha, Fab & Fix Connoisseur Off-Set Other: Greenteq Delta hinge protector and Nico Xtrabolt; GT Stay Guard; GT Securi-Clip or Snap-Lok (optional*); Fab & Fix Q318 Restrictor, Sash Seal, GT Bow Constrictor.
	Tilt/Turns	Locking: Maco face fit, Maco concealed gearing, Siegenia face fit, Siegenia concealed gearing, Roto Designo II concealed gearing Handles: Greenteq Alpha, Sensei T/T Handle Other: GT Securi-Clip or Snap-Lok (optional*) *Only where IGU size is increased by $\geq 4\text{mm}$
	Fixed windows	
	Multilight windows consisting of opening light(s) and/or fixed light(s)	

First Issued: 2001-11-09

Latest Issue: 2019-08-01

Effective Date: 2019-08-01

Expiry Date: 2022-07-31

Page: 6 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.
To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).

BSI Assurance UK Limited, registered in England under number 7805321 at 389 Chiswick High Road, London W4 4AL, UK.
A member of BSI Group of Companies.

Kitemark™ Certificate

No. KM 60733

Size Limitations and Performance Characteristics Traditional 2500 Series PVC-U Window System

Window Type	Length (mm) - Maximum	Height (mm) - Maximum	Area(m ²) - Maximum	Friction Stays (up to and including)	Transom/Mullion Length (mm) inc frame - Maximum	Air Permeability classification	Watertightness classification	Resistance to Wind classification	Exposure category as given in Table 1 of BS 6375-1:2009
Overall dimensions for windows with approved sash profiles:									
Projecting top hungs Reinforced*	1200	1200	-	24"	-	3	E1050	A5	2000
Projecting top hungs Reinforced*	1200	1500	-	24"	-	4	E1050	A5	2000
Projecting side hungs Reinforced*	700	1400	-	16"	-	4	7A	A5	2000
Projecting side hung Defender Plus hinge, reinforced*	900	1400	-	16"	-	4	7A	A5	2000
Tilt/Turns Steel reinforced sash	1500	1500	-	-	-	4	8A	A5	2000
Overall dimensions for windows with approved outer frame profiles:									
Fixed Reinforced*	2000	2000	4.00	-	-	3	9A	A5	2000
Overall dimensions for approved outer frames & transom/mullion profiles:									
Multilight steel T/M Reinforcement	2400	2400	3.36	-	1400	4	9A	A5	2000

* unless otherwise stated reinforcement can be either TCI, aluminium or steel.

First Issued: 2001-11-09

Latest Issue: 2019-08-01

Effective Date: 2019-08-01

Expiry Date: 2022-07-31

Page: 7 of 7

This certificate has been issued by and remains the property of BSI Assurance UK Ltd, Kitemark Court, Davy Avenue, Knowlhill, Milton Keynes MK5 8PP, United Kingdom and should be returned immediately upon request.

To check its validity telephone +44 (0) 345 080 9000. An electronic certificate can be authenticated [online](#).